



SPINA
HERRINGBONE PATTERN

SPINA 30°/45°

Incollato 2 strati spessore 10/15 mm di cui 3/4,2 mm nominali di strato nobile. La contro bilanciatura è in multistrato di betulla fenolica. La tipologia di posa è incollato e ben si adatta agli impianti di riscaldamento radianti a pavimento.

SPECIFICHE TECNICHE

La larghezza 140 viene prodotta F+F con verghette per la posa
Le larghezze 90 e 120 vengono prodotte M+F




30/45 DEGREE HERRINGBONE

The board is composed of two layers, its thickness is 10/15 mm, with 3/4.2 mm of hardwood. The counterbalancing layer is made of birch plywood with phenolic film. This board is suitable for glued installation and fits well to be installed onto screeds with underfloor heating.

TECHNICAL DATA

The 140 mm width is produced as F+F with rods for laying.
The 90 and 120 mm widths are produced as M+F.

DIMENSIONE DIMENSIONS	ESSENZA WOOD SPECIES	FINITURA FINISH
Spessore Thickness 10/15 mm Larghezza Width 90/120/140 mm Lunghezza Length 540/600 mm	Rovere Oak	
Spessore Thickness 15 mm Larghezza Width 120/140 mm Lunghezza Length 540/720 mm	Rovere, Noce, Noce Americano, Frassino, Olmo, Teak Oak, Walnut, American Walnut, Ash, Elm, Teak	





SPINA 90°

Incollato 2 strati spessore 10/15 mm di cui 3/4,2 mm nominali di strato nobile. La contro bilanciatura è in multistrato di betulla fenolica. La tipologia di posa è incollato e ben si adatta agli impianti di riscaldamento radianti a pavimento.

SPECIFICHE TECNICHE






La larghezza 140 viene prodotta F+F con verghette per la posa
Le larghezze 90 e 120 vengono prodotte M+F

90 DEGREE HERRINGBONE

The board is composed of two layers, its thickness is 10/15 mm, with 3/4.2 mm of hardwood. The counterbalancing layer is made of birch plywood with phenolic film. This board is suitable for glued installation and fits well to be installed onto screeds with underfloor heating.

TECHNICAL DATA

The 140 mm width is produced as F+F with rods for laying.
The 90 and 120 mm widths are produced as M+F.

DIMENSIONE DIMENSIONS	ESSENZA WOOD SPECIES	FINITURA FINISH
Spessore Thickness 10/15 mm Larghezza Width 90/120/140 mm Lunghezza Length 540/600 mm	Rovere Oak	    
Spessore Thickness 15 mm Larghezza Width 120/140 mm Lunghezza Length 540/720 mm	Rovere, Noce, Noce Americano, Frassino, Olmo, Teak Oak, Walnut, American Walnut, Ash, Elm, Teak	